

**AMENDMENTS TO THE CLAIMS:**

1.-43. *(Cancelled)*

44. *(Previously Presented: Copied from US Patent 6,565,605, Claim 1)* A prosthesis for the replacement of at least two facets located on a mammalian vertebra, comprising: at least one bone contacting surface that is adapted to be secured to a surface of the vertebra; at least two bearing surfaces for articulating with other facets, said at least two bearing surfaces being connected to said at least one bone contacting surface; and wherein no portion of said prosthesis is supported by the lamina of the vertebra.

45. *(Previously Presented: Copied from US Patent 6,565,605, Claim 2)* The device of claim 44 further comprising fixation elements for securing said at least one bone contacting surface to the vertebra.

46. *(Previously Presented: Copied from US Patent 6,565,605, Claim 3)* The device of claim 45 wherein said fixation elements are screws.

47. *(Previously Presented: Copied from US Patent 6,565,605, Claim 4)* The device of claim 44 wherein said at least bone contacting surface is porous coated to allow for bone ingrowth.

48. *(Previously Presented: Copied from US Patent 6,565,605, Claim 5)* The device of claim 47 wherein said porous coating includes at least one from a group comprising osteoinductive and osteoconductive substances.

49. *(Previously Presented: Copied from US Patent 6,565,605, Claim 6)* The device of claim 44 wherein said bearing surfaces are formed from a material selected from the group consisting of a ceramic, a metal and a polymer.

50. *(Previously Presented: Copied from US Patent 6,565,605, Claim 7)* The device of claim 44 wherein said prosthesis is configured so that said at least two bearing surfaces are adapted to replace a pair of inferior facets.

51. *(Cancelled)*

52. *(Cancelled)*

53. *(Cancelled)*

54. *(Previously Presented: Copied from US Patent 6,565,605, Claim 11)* A method for replacing at least two facets on a mammalian vertebra, comprising the steps of: resecting a pair of facets on the vertebra; and attaching a prosthesis to the vertebra so that a pair of bearing surfaces on the prosthesis are positioned in place of the resected facets, wherein the prosthesis is configured so that no portion of said prosthesis is supported by the lamina of the vertebra.

55. *(Previously Presented: Copied from US Patent 6,565,605, Claim 12)* A method for replacing facets on two adjacent vertebra, comprising the steps of: resecting at least a bony portion of the inferior facets of a superior vertebra; attaching a first prosthesis that replaces said inferior facets of said superior vertebra; resecting at least a bony portion of the superior facets of an inferior vertebra; and attaching a second prosthesis that replaces said superior facets of said inferior vertebra; wherein no portion of said first prosthesis is supported by the lamina of said superior vertebra, and further wherein no portion of said second prosthesis is supported by the lamina of said inferior vertebra.

56. *(Cancelled)*

57. *(Cancelled)*

58. *(Previously Presented: Copied from US Patent 6,565,605, Claim 15)* A prosthesis for the replacement of a pair of spinal facets, said prosthesis comprising: a first vertical member having a first end and a second end, said first end being adapted for disposition against, and attachment to, a first pedicle of a vertebra, and said second end comprising a bearing surface for engagement with a facet of an adjacent vertebra; a second vertical member having a first end and a second end, said first end being adapted for disposition against, and attachment to, the other pedicle of the vertebra, said second end comprising a bearing surface with a facet of an adjacent vertebra; and a bridge connecting said second end of said first vertical member to said second end of said second vertical member.

59. *(Previously Presented: Copied from US Patent 6,565,605, Claim 16)* The prosthesis of claim 58 wherein said first vertical member, said second vertical member and said bridge are formed so that said prosthesis is displaced from the lamina of the vertebra when said first end of said first vertical member is disposed against, and attached to, the first pedicle of a vertebra and said first end of said second vertical member is disposed against, the attached to, the other pedicle of the vertebra.

60. *(Previously Presented: Copied from US Patent 6,565,605, Claim 17)* A spinal implant kit for the replacement of facets, said implant kit comprising: a superior facet prosthesis adapted to replace two superior facets; an inferior facet prosthesis adapted to replace two inferior facets; wherein no portion of said superior facet prosthesis is supported by a lamina of a vertebra; and wherein no portion of said inferior facet prosthesis is supported by a lamina of a vertebra.

61. *(Previously Presented: Copied from US Patent 6,565,605, Claim 18)* A prosthesis for the replacement of a pair of spinal facets, said prosthesis comprising: a first vertical member having a first end and a second end, said first end being adapted for disposition against, and attachment to, a first pedicle of a vertebra, and said second end comprising a bearing surface for engagement with a facet of an adjacent vertebra; a second vertical member having a first end and a second end, said first end being adapted for disposition against, and attachment to, the other pedicle of the vertebra, said second end comprising a bearing surface with a facet of an adjacent vertebra; and a bridge connecting said first vertical member to said second vertical member; wherein said first vertical member, said second vertical member and said bridge are formed so that said prosthesis is displaced from the lamina of the vertebra when said first end of said first vertical member is disposed against, and attached to, the first pedicle of a vertebra and said first end of said second vertical member is disposed against, and attached to, the other pedicle of the vertebra.

62.-74. *(Cancelled)*.